



NEW PRODUCT FORT

JUNI 2026

PRICELIST



fortindo.id | fortindostore.id






Description			Cable Size (mm)	Type	Price / set (Rp)	Certificate Test Report
<p>TERMINAL KIT 1224KV</p>	12/20 (24)kV INDOOR	3 - Core	35-70	FNLS-20/3.1	1,969,000	<p>12/20(24)kV</p>
			95-150	FNLS-20/3.2	2,156,000	
			185-300	FNLS-20/3.3	2,344,000	
			400-630	FNLS-20/3.4	2,531,000	
	12/20 (24)kV OUTDOOR	3 - Core	35-70	FWLS-20/3.1	2,156,000	
			95-150	FWLS-20/3.2	2,344,000	
			185-300	FWLS-20/3.3	2,531,000	
			400-630	FWLS-20/3.4	2,719,000	
12/20 (24)kV INDOOR	1 - Core	35-70	FNLS-20/1.1	750,000		
		95-150	FNLS-20/1.2	844,000		
		185-300	FNLS-20/1.3	938,000		
		400-630	FNLS-20/1.4	1,031,000		
12/20 (24)kV OUTDOOR	1 - Core	35-70	FWLS-20/1.1	844,000		
		95-150	FWLS-20/1.2	938,000		
		185-300	FWLS-20/1.3	1,031,000		
		400-630	FWLS-20/1.4	1,125,000		
<p>TERMINAL KIT 1224KV</p>	6/12 (15)kV INDOOR	3 - Core	25-50	FNLS-12/3.1	891,000	<p>6/12(15)kV</p>
			70-120	FNLS-12/3.2	984,000	
			150-240	FNLS-12/3.3	1,078,000	
			300-400	FNLS-12/3.4	1,172,000	
	6/12 (15)kV OUTDOOR	3 - Core	25-50	FWLS-12/3.1	984,000	
			70-120	FWLS-12/3.2	1,078,000	
			150-240	FWLS-12/3.3	1,172,000	
			300-400	FWLS-12/3.4	1,266,000	
6/12 (15)kV INDOOR	1 - Core	25-50	FNLS-12/1.1	422,000		
		70-120	FNLS-12/1.2	469,000		
		150-240	FNLS-12/1.3	516,000		
		300-400	FNLS-12/1.4	563,000		
6/12 (15)kV OUTDOOR	1 - Core	25-50	FWLS-12/1.1	469,000		
		70-120	FWLS-12/1.2	516,000		
		150-240	FWLS-12/1.3	563,000		
		300-400	FWLS-12/1.4	609,000		

Aluminium Jointing & Cable Lugs Shear Bolt



Description	Cable Size (mm)	Type	Price / set (Rp)	Certificate Test Report
Connector / Jointing Shear Bolt <ul style="list-style-type: none"> * Material Aluminium Alloy * Plating tickness 15 micron * Testing Report standard IEC61238-1-3 	35 - 120	AMB-35-120	186,000	<p>Yuang Kibex Electric Co., Ltd Inspection report</p>
	150 - 300	AMB-150-300	315,000	
Cable Lugs Shear Bolt <ul style="list-style-type: none"> * Material Aluminium Alloy * Plating tickness 15 micron * Testing Report standard IEC61238-1-3 	35 - 120	BLMT-35-120	155,000	
	150 - 300	BLMT-150-300	325,000	






Jointing Kit Coldshrink

Description			Cable Size (mm)	Type	Price / set (Rp)	Certificate Test Report
	12/20 (24)kV	3 - Core	35-70	FJLS-20/3.1	5,196,000	
			95-150	FJLS-20/3.2	6,078,000	
			185-300	FJLS-20/3.3	6,961,000	
			400-630	FJLS-20/3.4	7,941,000	
	12/20 (24)kV	1 - Core	25-50	FJLS-20/1.1	2,059,000	
			70-120	FJLS-20/1.2	2,206,000	
			150-240	FJLS-20/1.3	2,353,000	
			300-400	FJLS-20/1.4	2,500,000	
	6/12 (15)kV	3 - Core	25-50	FJLS-12/3.1	3,529,000	
			70-120	FJLS-12/3.2	3,725,000	
			150-240	FJLS-12/3.3	3,922,000	
			300-400	FJLS-12/3.4	4,118,000	
	6/12 (15)kV	1 - Core	25-50	FJLS-12/1.1	1,424,000	
			70-120	FJLS-12/1.2	1,499,000	
			150-240	FJLS-12/1.3	1,574,000	
			300-400	FJLS-12/1.4	1,649,000	

Deadbreak - Elastimold



Description			Cable Size (mm)	Type	Price / set (Rp)	Certificate Test Report
	Deadbreak Tee Connector (Elastimold)	20(24)kV / 630A	30 - 50	FQJT-20/3.1	5,100,000	
			70 - 95	FQJT-20/3.2	5,100,000	
			120 - 150	FQJT-20/3.3	5,100,000	
			185 - 240	FQJT-20/3.4	5,100,000	
			300	FQJT-20/3.5	5,100,000	
			400	FQJT-20/3.6	5,100,000	

Lightning Striker Counter



Description	Display	Type	Price (Rp)
 <p>Analog Lightning Striker Counter * Min. current sensitivity : 350A * Max. detectable current : 100kA * Dimension installation hole : 30mm * Protection : IP66</p>	6 Digit (0-999999)	FLRC-S/II	1,975,000
 <p>Analog Lightning Striker Counter * Min. current sensitivity : 350A * Max. detectable current : 100kA * Dimension installation hole : 40mm * with reset press button * Protection : IP65</p>	4 Digit (0-9999)	FRLRC-S/R-43	2,385,000
 <p>Digital Lightning Striker Counter * Power Voltage : 220VAC * Min. Current Sensitivity : 0.1kA (8/20us) * Dimension Installation Hole : 9mm * with reset press button * Protection : IP20</p>	4 Digit (0-9999)	FLRC-D	2,897,000

Electronic Energy Meter

(Kwh Meter) Communication with moudbus RS485

Description	Rate Current (A)	Type	Price (Rp)
 <p>1 Phase, 2wire/50Hz * Class 1.0 * Direct connection 220VAC * with moudbus RS485</p>	5 (100)A	XTM75SC-S	605,000
 <p>3 Phase, 4wire/50Hz * Class 1.0 * Direct connection 3X220/380VAC * with moudbus RS485</p>	5 (100)A	XTM1250SC-S	1,568,000
	by CT../5A	XTM1250SCCT-S	1,568,000


Busbar Support

Description	Size for Busbar Copper (mm)	Type	Price (Rp)
 <p>Busbar Support 3Pole * Include Long screw 4set</p>	2*10 / 1*10	FBS-610	216,000
 <p>Busbar Support 4Pole * Include Long screw 5set</p>	2*10 / 1*10	FBS-810	306,000

Cabel Schoen - 2 Lobang

Description			Cable Size (mm)	Type	Price (Rp)
	Cable Schoen Copper (Cu)	2 hole	35 - 8	DTS35-2-8	60,600
			50 - 10	DT50-2-10	100,800
			70 - 10	DTS70-2-10	129,600
			95 - 12	DTS95-2-12	153,600
			120 - 12	DTS120-2-12	187,200
			150 - 12	DTS150-2-12	244,800
			185 - 16	DTS185-2-16	331,200
			240 - 16	DTS240-2-16	384,000
			300 - 16	DTS300-2-16	556,800
	Cable Schoen Bimetal (AL-Cu)	2 hole	50 - 10	DTSL50-2-10	54,000
			70 - 12	DTLS70-2-12	76,300
			95 - 12	DTLS95-2-12	96,000
			120 - 12	DTLS120-2-12	115,700
			150 - 14	DTLS150-2-14	141,400
			185 - 14	DTLS185-2-14	180,000
			240 - 14	DTLS240-2-14	225,400
			300 - 16	DTLS300-2-16	308,600
	Cable Schoen Alluminium (AL)	2 hole	35 - 8	DLS35-2-8	14,600
			50 - 10	DLS50-2-10	16,300
			70 - 12	DLS70-2-12	20,200
			95 - 12	DLS95-2-12	27,000
			120 - 12	DLS120-2-12	35,200
			150 - 14	DLS150-2-14	41,200
			185 - 14	DLS185-2-14	51,500
			240 - 14	DLS240-2-14	61,700
			300 - 16	DLS300-2-16	107,200

CUTTING TOOLS DIN - RAIL MCB

Description	Rail MCB Tickness (mm)	Type	Price (Rp)
 <p>Alat Pemotong Rail MCB (Alluminium & Besi) * Rail MCB 1 Fungsi * Rail MCB 2 Fungsi</p>	0.7 - 1.5mm	FDRC-1/2	1,500,000

Component Medical Safety Power System

Description		Type	Price (Rp)	
	Isolation Transformer - Single Phase 220VAC	3.15kVA	KD20P50 3.15KVA	33,000,000
		5kVA	KD20P50 5KVA	36,667,000
		6.3kVA	KD20P50 6.3KVA	41,250,000
		8kVA	KD20P50 8KVA	43,083,000
		10kVA	KD20P50 10KVA	45,833,000
	Isolation Transformer - Three Phase 380VAC	10kVA	KD20P50 10KVA/3	64,167,000
		15kVA	KD20P50 15KVA/3	73,333,000
20kVA		KD20P50 20KVA/3	82,500,000	
	Power Supply Input : 110 - 250VAC	5VDC	KD20P50 4005	1,650,000
		15VDC	KD20P50 4015	1,650,000
	Insulation Monitor	LCD Display	KD20P50 2023	25,667,000
	KWIS Intelligent Terminal	LED Display	KD20P50 5200	4,767,000
		LCD Display	KD20P50 5301	5,767,000
	KWIS Intelligent Terminal (central alarm)	7 inch	KD20P50 5507	32,817,000
		10 inch	KD20P50 5510	44,092,000
	Insulation Fault Evaluation Instrument	LCD Display	KD20P50 6000	12,833,000
	Insulation Fault Locator	4 channels	KD20P50 6104	12,833,000
		8 channels	KD20P50 6108	14,667,000
		12 channels	KD20P50 6112	16,500,000
	Gateway	128 I/O	KD20P50 7100	4,125,000
	Current transformer	0.66kV	KD20P50 3181	802,000
	Insulation Fault location transformer	0.66kV	KD20P50 3182	802,000